



F-412



2.25-17 2.75-17
2.75-18 3.00-18REINF
3.00-18TL 2.00-19



F-413



3.25-16 2.50-17
2.50-18



F-414



2.50-18



F-418



3.00-18 REINF
3.00-18 TL



F-421



2.25-17



F-422



3.50-16 REINF
2.50-17



F-423



2.75-17 REINF



F-424



3.00-17 REINF
3.25-17 REINF



F-425



3.00-17 REINF



F-431



3.00-12
2.50-18



F-432



2.75-18 REINF



F-433



3.00-18REINF
3.00-18TL



F-434



3.25-18REINF
3.25-18TL



F-435



2.50-9



F-437



2.50-17



F-441



3.25-16 REINF



F-446



4.00-14 REINF
3.00-16 REINF



F-463



3.25-18 REINF 3.25-18 TL
90/90-18 REINF
90/90-18 TL



F-501



3.00-8



F-502



3.00-10



F-503



3.00-10
130/60-13 130/60-13TL



F-504



3.50-8



F-505



3.50-10



F-506



3.50-10



F-507



2.50-14	2.50-18 REINF
3.00-12	3.00-16 REINF



F-508



3.50-10(TL)



F-511



2.75-18 REINF



F-513



2.75-18 REINF
3.00-18 REINF



F-514



3.00-17 REINF



F-551



90/90-10	3.00-10
90/90-10TL	3.00-10T2



F-552



3.50-10
3.50-10TL



F-553



100/80-10 TT(TL)
100/90-10 TT(TL)
120/90-12 TT(TL)
3.50-10 TT(TL)
4.00-12 TT(TL)



F-554



2.50-17
2.75-17 REINF
2.75-14



F-558



3.50-8
4.00-8



F-560



4.00-8



F-561



2.75-16 REINF



F-562



3.00-16 REINF



F-564



2.75-17 REINF 2.75-17TL
2.75-18 REINF 2.75-18TL



F-565



90/90-18 REINF



F-567



3.50-10 3.50-10TL



F-569



3.50-16 3.50-16TL



F-581



2.75-14



F-582



3.00-12



F-583



2.25/2.50-14
3.00-14



F-586



3.00-17 REINF



F-602



80/100-18 REINF



F-609



3.50-10 3.50-10TL



F-610



3.00-10
3.00-10 TL



F-621



4.00-8 TT(TL)
130/70-12 TT(TL)
120/70-12 TT(TL)
110/90-12 TT(TL)
120/80-12 TT(TL)



F-622



130/70-12



F-623



100/60-12



F-631



130/90-15 REINF
130/90-15TL



F-632



100/90-10	100/90-10TL
110/80-10	110/80-10TL



F-641



100/90-18REINF
100/90-18TL



F-651



3.50-10
3.50-10TL



F-653



90/90-18 REINF
90/90-18TL



F-654



3.50-8



F-655



90/90-12
80/100-14



F-661



90/90-18REINF
90/90-18TL
3.00-10



F-662



90/90-18REINF
90/90-18TL



F-663

110/90-16REINF
110/90-16TL



F-664

110/90-16REINF
110/90-16TL



F-665

130/90-15REINF
130/90-15TL



F-666

120/90-16
120/90-16TL

摩托车轮胎规格花纹索引
DETAILS OF MOTORCYCLE TYRES

产品分类 DESCRIPTION	产品规格 SIZE	花纹编号 PATT NO.
摩托车胎	100/60 - 12	F623
	100/80 - 10	F553
	100/80 - 16	F667
	100/90 - 10	F553 F632
	100/90 - 18	F641
	110/80 - 10	F632
	110/90 - 10	F665
	110/90 - 12	F621
	110/90 - 16	F663 F664
	120/70 - 12	F621
	120/80 - 12	F621
	120/90 - 12	F553
	120/90 - 16	F666
	130/60 - 13	F503
	130/70 - 12	F621 F622
130/90 - 15	F631 F665	



F-667

90/90-17 100/80-16REINF
90/90-17TL 100/80-16TL



F-669

3.00-18REINF



F-903

4.00-8

产品分类 DESCRIPTION	产品规格 SIZE	花纹编号 PATT NO.
摩托车胎	3.00 - 17	F424 F425 F586 F514
	3.00 - 18	F412 F418 F433 F669
	3.25 - 16	F413 F441
	3.25 - 17	F424
	3.25 - 18	F434 F463
	3.50 - 8	F504 F558 F654
	3.50 - 10	F505 F506 F508 F522 F553 F567 F609 F651
	3.50 - 16	F422 F569
	4.00 - 8	F558 F560 F621
	4.00 - 12	F553
	4.00 - 14	F446
	80/100-14	F655
	80/100 - 18	F602
	90/90 - 10	F551
	90/90 - 12	F655
90/90 - 17	F667	

产品分类 DESCRIPTION	产品规格 SIZE	花纹编号 PATT NO.
摩托车胎	2.00 - 19	F412
	2.25 - 14	F583
	2.25 - 17	F412 F421
	2.50 - 9	F435
	2.50 - 14	F507 F583
	2.50 - 17	F413 F422 F437 F554
	2.50 - 18	F413 F414 F431 F507
	2.75 - 14	F554 F581
	2.75 - 16	F561
	2.75 - 17	F412 F423 F554 F564
	2.75 - 18	F412 F432 F511 F513 F564
	3.00 - 8	F501
	3.00 - 10	F503 F502 F551 F610 F661
	3.00 - 12	F431 F507 F582
	3.00 - 14	F583
3.00 - 16	marketing@0686parts.com	

TEMCO INTERNATIONAL LIMITED

软边车胎 B/E



F-101



28x1 1/2



F-102



28x1 1/2



F-103



26X1 3/4



F-104



26X1 3/4

24X1 3/4



F-106



26x1 1/2



F-109



24x1 3/4



F-153



28X1 1/2

26X1 3/4



F-162



28X1 1/2

直边车胎w/o



F-167



26X2 1/2



F-111



40-635(28X1 1/2)



F-114



32-630(27X1 1/4)



F-115



37-590(26X1 3/8)



F-142



37-540(24X1 3/8)
37-590(26X1 3/8)



F-151



37-540(24X1 3/8)
37-590(26X1 3/8)



F-152



40-635(28X1 1/2)
37-590(26X1 3/8)



F-154



37-540(24X1 3/8)
37-590(26X1 3/8)



F-158



40-590(26X1 1/2)



F-159



37-540(24X1 3/8)
37-590(26X1 3/8)



F-160



37-540(24X1 3/8)
37-590(26X1 3/8)



F-164



37-590(26X1 3/8)



F-175



37-590(26X1 3/8)
37-540(24X1 3/8)



F-181



28X1.75



F-182



28X1.75



F-211



40-330(16X1 1/2)

钩边车胎 H/E



F-372



37-590(26X1 3/8)



F-373



37-622(700X35c)
40-622(700X38c) (UB65)



F-141



20X1.75
24X1.75



F-155



24X1.50
26X1.50



F-157A



22X1.75
24X1.75



F-158



24X1.50



F-166



20X1.75
24X1.75



F-168



22X1.75
24X1.75
26X2.125



F-176



24X1.75
22X1.75
20X1.75



F-201



24X1.75 24X1.95
26X1.75 26X1.95



F-202



24X1.95




F-203



26X1.75


 <p>F-204</p>	 <p>F-205</p>	 <p>F-206</p>	 <p>F-207</p>
<p>26X1.95 26X2.125</p>	<p>24X1.50 26X1.50</p>	<p>26X1.75 24X1.95</p>	<p>26X1.75</p>
 <p>F-208</p>	 <p>F-209</p>	 <p>F-211</p>	 <p>F-218</p>
<p>26X1.95</p>	<p>26X1.95</p>	<p>22X1.75</p>	<p>26X1.50</p>
 <p>F-251</p>	 <p>F-253</p>	 <p>F-259</p>	 <p>F-263</p>
<p>24X1.95 26X1.95 20X1.95 20X2.125</p>	<p>26X1.95</p>	<p>44-584(26X1 5/8X1 1/2) 26X1.75</p>	<p>26X2.125 26X2.40 26X1.95 26X2.35</p>



F-264 


24X1.95
24X2.125



F-266 山地 Mountain 


26X1.95



F-270 雪地 Snow 

26X1.95



F-286 


28X1.75



F-301 

20X2.125
20X1.75
16X2.125
16X1.75
18X1.75
14X2.125
12 1/2X2 1/4
14X1.75



F-302 


16X1.75
20X1.75



F-303 


14X1.75
16X1.75
20X1.75



F-304 


14X1.75



F-305 

18X1.75



F-306 


20X2.50



F-351 

14X1.75



F-352 

16X1.75
16X2.125



F-353



18X1.75



F-354



20X1.75



F-355(A)



18X1.95 18X2.125 20X1.95
20X2.125 20X2.125 (2.35)
24X2.125 (2.35) 26X2.125 (2.35)



F-361



16X2.125
12X2.25



F-362



16X1.75
18X1.75
20X1.75



F-363



20X1.75
16X1.75 18X1.75



F-371



20X1.75



F-375



20X1.95



TT-606



26X2.0



TT-703



20X1.95



UB53



16X1.75
20X1.75



UB63



24X1.90
26X1.90

游艺车胎 CHILDREN BARROW'S TYRE



UB69

26X1.90	24X1.90
12 1/2X1.75X2 1/4	
20X1.90	16X1.75
14X1 3/8X1 5/8	



UB70

24X1.90
20X1.90



F-001

4 1/2X1
6X1 1/4



F-352

8.5X2
10X2

自行车轮胎规格花纹索引 DETAILS OF BICYCLE TYRES



F-356

6X114

产品分类 DESCRIPTION	产品规格 SIZE	花纹编号 PATT NO.	产品分类 DESCRIPTION	产品规格 SIZE	花纹编号 PATT NO.
软边车胎	26X11/2	F106	直边车胎	37-540 (24X13/8)	F142 F151 F154 F159 F160 F175
	28X11/2	F101 F102 F153 F162		37-590 (26X13/8)	F115 F142 F151 F154 F159 F160 F164 F175 F372 F152
	24X13/4	F104 F109		37-622 (700X35C)	F373
	26X13/4	F103 F104 F153		40-330 (16X11/2)	F211
	26X21/2	F167		40-590 (26X11/2)	F158
41/2X1	F001	40-622 (700X38c)		UB65	
游艺车胎	6X11/4	F356		40-635 (28X11/2 28X11/2X13/8)	F111 F152
	8.5X2	F352 F001		44-584 (26X15/8X1 1/2)	F259
	10X2	F352		47-203 (121/2X1.75X21/4)	UB69
直边车胎	32-630 (27X11/4)	F114			
	14X13/8X15/8	UB69			

产品分类 DESCRIPTION	产品规格 SIZE	花纹编号 PATT NO.
直边车胎	47-622 (28X1.75)	F181 F182
	62-203 (121/2X11/4)	F301
勾边车胎	24X1.50 (40-507)	F205 F155 F158
	26X1.50 (40-559)	F205 F218 F155
	14X1.75 (47-254)	F301 F303 F304 F351
	16X1.75 (47-305)	F301 F302 F303 F352 F362 F363 UB53 UB69
	18X1.75 (47-355)	F301 F305 F353 F362 F363
	20X1.75 (47-406)	F141 F301 F302 F303 F354 F166
		F176 UB53 F371 F362 F363
	22X1.75 (47-457)	F211 F157A F168 F176
	24X1.75 (47-507)	F141 F201 F157A F166 F168 F176
	26X1.75 (47-559)	F201 F203 F206 F207 F259
	28X1.75 (47-611)	F286
	20X1.90 (51-406)	UB69 UB70
	24X1.90 (51-507)	UB70 UB63 UB69
	26X1.90 (51-559)	UB63 UB69
18X1.95 (53-355)	F355	

产品分类 DESCRIPTION	产品规格 SIZE	花纹编号 PATT NO.
勾边车胎	20X1.95 (53-406)	F251 F355 TT703 F375
	24X1.95 (53-507)	F201 F202 F206 F251 F264
	26X1.95 (53-559)	F201 F204 F208 F209 F251 F253 F263 F266 F270
	26X2.0 (54-559)	TT606
	14X2.125 (57-254)	F301
	16X2.125 (57-305)	F301 F352 F361
	18X2.125 (57-355)	F355
	20X2.125 (57-406)	F251 F301 F355 F355A
	24X2.125 (57-507)	F264 F355A
	26X2.125 (57-559)	F204 F263 F168 F355A
	12X2.25 (60-203)	F361
	20X2.35 (63-406)	F355A
	24X2.35 (63-507)	F355A
	26X2.35 (63-559)	F355A F263
	26X2.40 (64-559)	F263
	20X2.50 (67-406)	F306

TEMCO INTERNATIONAL LIMITED

marketing@0086parts.com



F-700



F-701



F-702



F-703

ATV车胎技术参数 ALL-TERRAIN VEHICLE TIRE

序号	产品规格 SIZE	花纹编号 PATT.NO.	层级 P.R.	外直径 O.D(mm)	断面宽 S.W.(mm)	轮辋 RIM WIDTH (英寸INCH)
1	16×8.0-7	F-700	2PR	404	186	6.50
2	19×7-8	F-701	2PR	483	172	5.50
3	18×9.50-8	F-712	2PR	462	235	7.00
4	17×8.0-8	F-703	2PR	432	197	6.50
5	20×7-8	F-704	2PR	508	177	5.50
6	14.5×7-6	F-700	2PR	368	177	5.50
7	13×5.00-6	F-702	4PR	320	122	3.50
8	15×6.00-6	F-702	4PR	366	155	4.50
9	16×6.50-8	F-702	4PR	406	165	5.375
10	18×8.50-8	F-702 F-705	4PR	450	213	7.00
11	20×10.00-8	F-702	4PR	508	254	8.00
12	23×8.50-12	F-702	6PR	574	213	7.00
13	23×10.50-12	F-702	6PR	579	264	8.50
14	26×12.00-12	F-702	8PR	648	307	10.50
15	13×4-6	F-713	4PR	340	100	3.0
16	4.10×5	F-713	4PR	268	102	3.25



F-704



F-705



F-712



F-713



F-951



F-952

拖车轮胎技术参数 TRAILER TIRE

轮胎规格 SIZE	花纹编号 PATT.NO.	标准轮辋 RIM WIDTH	层级 PLY RATING	气压 PSI	新胎充气尺寸 O.D		最大负荷 (LBS)
					断面宽 (INCH)	外直径/OD (INCH)	
9.00-20	F-951	7.0	12	670	259	1018	2340
10.00-20	F-951	7.5	14	700	278	1055	2740
11.00-20	F-951	8.0	14	700	293	1085	2995
12-16.5	F-952	9.75	12	75	12.10	32.20	3560(双胎) 4045(单胎)
6.90-9	F-952	5.50	6	60	690	21.46	1120
20.5X8-10	F-952	6.00	8	70	8.00	20.40	1330

房车轮胎技术参数 MOBILE-HOME TIRE

轮胎规格 SIZE	花纹编号 PATT.NO.	标准轮辋 RIM WIDTH	层级 PLY RATING	气压 PSI	新胎充气尺寸 O.D		最大负荷 (LBS)
					断面宽 (INCH)	外直径/OD (INCH)	
7-14.5	F-851	6.00	12	100	7.30	26.64	2335
8-14.5	F-851	6.00	10	85	8.00	27.80	2540
	F-852		12	100	9.50	28.00	2790
	F-853		12	100			3305
9-14.5	F-853	7.00	12	100			



F-851



F-852



F-853

TEMCO INTERNATIONAL LIMITED

marketing@0086parts.com



F-841 | F-842 | F-843 | F-844

**粘接式实芯技术参数
POWERTRAK SOLID TIRE WITH RIM JOINT**

轮胎规格 SIZE	花纹编号 PATT.NO.	花纹形式 PATT. TYPE	最大负荷 LBS
31x5x7	F-841	TR	5240
33x6x8	F-841	TR	6874
31x5x7	F-842	SM	5240
33x6x8	F-842	SM	6894
27x7x17 3/4	F-843	TR	6500
31X6X10(10-16.5)	F-844	TR	6595
33X6X11(12-16.5)	F-844	TR	7915

铲车轮胎技术参数 SKID-STEER TIRE

轮胎规格 SIZE	花纹编号 PATT.NO.	标准轮辋 RIM WIDTH	层级 PLY RATING	气压 PSI	新胎充气尺寸 O.D		最大负荷 (LBS)
					断面宽 (INCH)	外直径/OD (INCH)	
10-16.5	F-801	8.25	8	60	10.40	30.43	4140
	F-802						
	F-803						
	F-804						
	F-805						
12-16.5	F-801	9.75	8	50	12.10	32.73	4810
	F-802						
	F-803						
	F-804						
	F-805						
14-17.5	F-801	10.50	10	55	13.75	36.25	6850
15-19.5	F-801	11.75	10	50	15.30	40.12	8260
33X15.50-16.5	F-801	11.75	12	55	15.50	33.00	9760
23x8.5-12	F-801	7.00	6	50	8.40	22.60	1810



F-801 | F-802 | F-803 | F-804 | F-805

TEMCO INTERNATIONAL LIMITED

marketing@0086parts.com

粘接式实芯/铲车轮胎 19

POWERTRAK SOLID TIRE WITH RIM JOINT/SKID-STEER TIRE

**F-901****F-906****F-907****F-908****F-909****农用轮胎技术参数 AGRICULTURAL TIRE****F-2导向轮胎 ROTATION TIRE**

轮胎规格 SIZE	花纹编号 PATT.NO.	标准轮辋 RIM WIDTH	层级 PLY RATING	气压 PSI	新胎充气尺寸 O.D		最大负荷
					断面宽 (mm)	外直径/OD (mm)	
4.00-12	F-907	3.00	4	52	112	539	224
4.00-15	F-907	3.00	4	52	112	616	264
4.00-19	F-907	3.00	4	52	112	717	325
5.00-15	F-907	3.00	4	44	130	664	325
5.50-16	F-907	4.00	6	56	150	713	475
6.00-16	F-907	4.00	6	52	159	739	515
7.5L-15	F-907	6.00	6	44	2		650
7.50-18	F-907	5.50	6	44	203	859	730
9.5L-15	F-907	2.00	8	48	241	782	850
11L-15	F-907	8.0	8	44	279	813	950
11L-15M	F-908	8.0	10	52	279	813	1060

R-1驱动轮胎 DRIVE TIRE

轮胎规格 SIZE	花纹编号 PATT.NO.	标准轮辋 RIM WIDTH	层级 PLY RATING	气压 PSI	新胎充气尺寸 O.D		最大负荷
					断面宽 (mm)	外直径/OD (mm)	
7-14	F-911	6.00	6	36	183	691	450
7-16	F-911	6.00	6	36	183	742	500
8-16	F-911	6.00	6	28	211	790	615
8-18	F-911	6.00	6	28	211	841	670
4.00-12	F-901	3.00D	4	35	112	535	93
4.00-14	F-906	3.00D	4	50	110	590	123
6.00-12	F-901	4.50E	6	35	165	640	183
6.00-16	F-901	4.50E	6	35	165	745	225
7.50-16	F-901	5.50F	6	30	205	810	295
7.50-20	F-901	5.50F	6	30	205	910	345
11.2-24	F-909	W10	8	35	285	1105	556
14.9-24	F-909	W13	8	26	378	1265	799

**F-910****F-911****F-912****F-913****F-914**

**F-901****F-906****F-907****F-908****F-909****农用轮胎技术参数 AGRICULTURAL TIRE****I-1 农机具轮胎 TIRE FOR AG TRACTORS**

轮胎规格 SIZE	花纹编号 PATT.NO.	标准轮辋 RIM WIDTH	层级 PLY RATING	气压 PSI	新胎充气尺寸 O.D		最大负荷
					断面宽 (mm)	外直径/OD (mm)	
5.90-15	F-910	4.50	4	36	155	665	515
6.70-15	F-910	4.50	6	44	170	704	730
7.60-15	F-910	5.50	6	40	193	734	800
9.5L-14	F-910	7.00	8	44	241	741	1090
9.5L-15	F-910	7.00	8	44	241	767	1120
11L-14	F-910	8.00	6	28	279	752	925
11L-15	F-910	8.00	8	36	279	777	1150
11L-16	F-910	8.00	8	36	279	803	1215
12.5L-15	F-910	10.00	10	44	318	823	1550
12.5L-16	F-910	10.00	12	52	318	848	1800
16.5L-16.1	F-910	14.00	12	40	419	1024	2575

FI 农机具轮胎 TIRE FOR AG TRACTORS

轮胎规格 SIZE	花纹编号 PATT.NO.	标准轮辋 RIM WIDTH	层级 PLY RATING	气压 PSI	新胎充气尺寸 O.D		最大负荷
					断面宽 (mm)	外直径/OD (mm)	
9.5I-15	F-910	7.00	8	44	241	767	1120
11L-15	F-910	8.00	12	52	279	777	1450
12.5L-15	F-910	10.00	12	52	318	823	1750

农业、工业高通过性轮胎 TIRE FOR AG&INDUSTRY

轮胎规格 SIZE	花纹编号 PATT.NO.	标准轮辋 RIM WIDTH	层级 PLY RATING	气压 PSI	新胎充气尺寸 O.D		最大负荷
					断面宽 (mm)	外直径/OD (mm)	
27X8.50-15	F-801	7.00	8	60	213	678	825
27X10.50-15	F-801	8.50	6	45	259	691	750
26X12-12	F-912	10.50	8	50	307	648	1370
29X12.50-15	F-912	10.00	6	30	310	742	800
31X15.50-15	F-912	13.00	8	45	391	792	1250
12.5/80-18	F-914	9.00	12	54	308	985	
28X8.5-15	F-913	7.00	6	45	212	712	750

**F-910****F-911****F-912****F-913****F-914**



F-811



F-812



F-813



F-814

工业轮胎技术参数 (1) INDUSTRIAL TIRE

轮胎规格 SIZE	花纹 编号 PATT.NO.	标准轮辋 RIM WIDTH	层级 PLY RATING	气压 PSI	外缘尺寸		不同速度下的最大负荷 (LBS)								
					断面 宽/SW (INCH)	外直径 OD (INCH)	驱动轮 DRIVE		转向轮 ROTATION		其他车辆 OTHER				
							10MPH	15MPH	15MPH	20MPH	5MPH	15MPH	20MPH	30MPH	
4.00-8	F-813	2.50	6	105	4.25	16.64						1230	905	840	775
5.00-8	F-811	3.00	8	115	5.15	18.46	-	-	1830	1605	1830	1345	1250	1155	
	F-812		10	*125			-	-	1910	1675	1910	1405	1306	1207	
	F-813		12	*145			-	-	2084	1828	2084	1533	1425	1317	
6.00-9	F-811	4.00	10	125	6.3	21.46	3715	3340	2820	2480	2820	2080	1930	1780	
	F-812		12	150			4130	3715	3140	2760	3140	2315	2150	1985	
	F-813		10	115			4225	3805	3210	2825	3210	2365	2200	2030	
6.50-10	F-811	5.00	12	*125	7.00	23.50	4562	4110	3468	3053	3469	2557	2378	2195	
	F-812		14	*145			4976	4483	3783	3330	3784	2789	2594	2394	
	F-813		12	125			5995	5395	4555	4005	4555	3355	3115	2875	
7.00-12	F-811	5.00	14	145	7.57	26.88	6535	5885	4970	4365	4970	3660	3400	3140	
	F-812		16	*150			6639	5981	5052	4439	5056	3723	3460	3198	
	F-813		8	90			4960	4460	3780	3320	3780	2780	2580	2380	
6.50-16	F-811	5.00	10	*150	7.00	29.50	5255	4725	4008	3522	4011	2951	2740	2528	
			12	125			6870	6185	5220	4590	5220	-	-	-	
			14	145			7495	6745	5695	5005	5695	-	-	-	
7.00-15	F-811	5.50	16	*150	8.00	30.00	7622	6866	5799	5096	5804	-	-	-	
			12	115			7690	6920	5845	5135	5845	4305	4000	3690	
			14	*125			8073	7273	6143	5398	6148	4530	4210	3884	
7.50-15	F-811	6.00	16	*145	8.45	31.82	8805	7932	6699	5887	6705	4940	4592	4236	
			10	95			7150	6450	5440	4780	5440	4020	3720	3440	
			12	*115			7969	7192	6070	5333	6076	4492	4159	3848	
8.15-15	F-811	7.00	12	120	8.7	27.8	6880	6190	5230	4595	5230	3850	3575	3300	
	F-812		14	140			7530	6775	5720	5030	5720	4215	3915	3615	
	F-813		16	*150			7815	7040	5941	5220	5946	4385	4075	3767	
7.00-9	F-812	5.00	10	120	7.48	23.23	5029	4724	4008	3634	4107	3303	2863	2577	
8.25-12	F-813	6.50	12	110	9.25	30.12	8259	7477		5748	6497	5231	4537	4085	



F-811



F-812



F-813



F-814

工业轮胎技术参数 (2) INDUSTRIAL TIRE

轮胎规格 SIZE	花纹编号 PATT.NO.	标准轮辋 RIM WIDTH	层级 PLY RATING	气压 PSI	外源尺寸 OD		不同速度下的最大负荷 (LBS)								
					断面 宽/SW (INCH)	外直径 OD (INCH)	驱动轮DRIVE		转向轮ROTATION		其他车辆 OTHER				
							10MPH	15MPH	15MPH	20MPH	5MPH	15MPH	20MPH	30 MPH	
23 x 9-10	F-811	7.00	16	150	9.00	23.00	6700	6000	5080	4460	5080	3740	3480	3220	
			18	*160			6962	6233	5282	4637	5282	3881	3613	3343	
			20	*170			7203	6448	5464	4798	5464	4021	3744	3464	
			22	*180			7413	6678	5659	4969	5659	4158	3872	3582	
23 x 10.1-12	F-811	8.00	14	120	10	23.50	7250	6500	5500	4820	5500	4040	3760	3460	
	F-812		18	150			8250	7400	6250	5500	6250	4620	4280	3960	
			22	*170			8787	7887	6662	5896	6700	4950	4587	4244	
			12	105			7160	6445	5445	4785	5445	4010	3725	3440	
27 x 10-12	F-811	8.00	16	*135	10	26.86	8298	7475	6314	5548	6319	4656	4328	4000	
			20	*150			8827	7952	6716	5902	6722	4953	4604	4255	
			24	*160			9165	8256	6973	6125	6979	5143	4780	4418	
				26			150	14102	12705	10730	9429	10739	7914	7355	6798
28 x 12.5-15	F-811	9.75	26	150	13.00	28.00	17623	15877	13410	11784	13422	9891	9192	8496	
			32	160	12.00	32.50	18303	16489	13927	12238	13938	10272	9546	8823	
				16	135	9450	8500	7200	6300	7200	5300	4920	4540		
32 x 12.1-15	F-811	9.75	26	150	12.00	32.50	18303	16489	13927	12238	13938	10272	9546	8823	
				16			135	10100	9050	7650	6700	7650	5640	5240	4840
				26			170	10844	9717	8214	7205	8225	6070	5641	5214
				18			*130	14143	12673	10712	9397	10712	7916	7357	6800
250-15	F-811	7.50	20	135	11.81	33.08	14500	13100	11000	9700	11000	8100	7550	6950	
	F-812		26	*170			16589	14945	12559	11075	12585	9270	8640	7956	
			12	105			8680	7810	6595	5800	6595	4860	4515	4165	
			14	120			9385	8445	7135	6270	7135	5255	4880	4504	
300-15	F-811	8.00	16	*145	9.30	33.36	10446	9411	7948	6984	7955	5862	5448	5031	
				16			115	14910	13420	11330	9960	11330	8350	7755	7155
				20			*125	15563	14021	11862	10423	11872	5749	8131	7508
				26			*145	17005	15320	12939	11370	12950	9543	8869	8190
10.00-20	F-811	7.50	16	100	10.95	42.23	17095	15385	12995	11420	12995	9575	8890	8205	
				20			*125	19472	17542	14816	13019	14828	10927	10146	9369
				26			*145	21238	19134	16160	14200	16174	11919	11067	10219
				16			150	4724	4255	3594	3158	3597	2651	2461	2273
15 x 7-8	F-811	5.50	16	150	7.62	15.00	4083	3679	3107	2730	3110	2291	2128	1965	
				8			95	2965	2670	2255	1980	2255	-	-	-
				12			140	3720	3345	2825	2485	2825	-	-	-
				16			145	4695	-	3615	-	2885	-	D	-
16 x 6-8	F-811	4.33	16	150	6.68	16.00	3850	3468	2929	2578	2937	-	D	-	
				18			*150	5180	4660	3940	3460	3940	2900	2690	2480
				14			145	5257	4736	4014	3527	4017	2959	2745	2533
				18			*160	5462	4921	4170	3664	4174	3074	2852	2631
18 x 7-8	F-811	4.33	8	95	6.63	18.30	16800	13200	-	-	-	-	-		
	F-812		12	140			3720	3345	2825	2485	2825	-	-	-	
21 x 8-9	F-811	6.00	16	150	8.00	21.00	4695	-	3615	-	2885	-	D	-	
				18			*150	3850	3468	2929	2578	2937	-	D	-
				14			145	5180	4660	3940	3460	3940	2900	2690	2480
				16			*150	5257	4736	4014	3527	4017	2959	2745	2533
38 x 16-20	F-814	11.5	18	*160	16	38.5	5462	4921	4170	3664	4174	3074	2852	2631	
			32	150			16800	13200	-	-	-	-	-	-	

* : 高负荷 HIGH LOAD



F-821



F-822



F-823

充气式实芯轮胎技术参数 PNEUMATIC SOLID TIRE

轮胎规格(SIZE)	花纹编号 PATT.NO.	轮胎外缘尺寸		最大额定负荷 (LBS)	
		断面宽/SW INCH	外直径/OD INCH	负荷轮 (6MPH)	转向轮 (10MPH)
4.00-8/3.00	F-822	3.98	15.90		1685
4.00-8/3.75	F-822	4.76	16.54		1685
5.00-8/3.00	F-821 F-823	4.92	17.60		1935
6.00-9/4.00	F-821 F-823	5.71	20.24	4230	3065
6.00-9/4.00	F-821 F-823	6.02	20.31	4230	3065
7.00-9/4.5	F-821	6.50	22.44	6013	5738
7.00-9/5.0	F-821	6.50	22.44	6013	5738
6.50-10/5.0	F-821 F-823	6.34	22.05	5810	4210
7.00-12/5.0	F-821 F-823	6.93	25.31	6640	4810
7.00-12/5.0	F-821 F-823	7.09	25.31	6640	4810
6.50-16/5.5	F-821	7.15	30.18	6415	4645
7.00-15/5.5	F-821 F-823	7.80	27.09	7905	5725
7.50-10/5.0	F-821	7.28	24.88	6460	4675
7.50-15/5.5	F-821	7.95	31.22	10195	7385
7.50-15/6.0	F-821	7.95	31.22	10195	7385
7.50-15/6.5	F-821	7.95	31.22	10195	7385
7.50-16/5.5	F-821	8.07	31.38	8515	6240
7.50-16/6.0	F-821	8.07	31.38	8515	6240
7.50-20/6.0	F-821	8.07	31.38	10630	7695
8.00-16/5.5	F-821	8.18	31.50	9200	6665
8.15-15/7.0	F-821 F-823	8.90	27.00	9000	6520
8.25-15/6.5	F-821 F-823	8.15	31.22	10875	7875
8.25-12/6.5	F-821	8.07	28.78	8259	7478
9.00-16/6.5	F-821	8.35	31.50	9200	6665
9.00-10/7.0	F-821	9.25	27.95	7920	6020
9.00-20/6.5	F-821	10.04	39.61	13200	9560
9.00-20/7.0	F-821	10.04	39.61	13200	9560
10.00-20/7.5	F-821	10.83	41.10	13825	10010
10.00-20/8.0	F-821	10.83	41.10	13825	10010
10.00-20/8.0	F-822	10.83	41.10	13825	10010
12.00-20/8.0	F-821	11.73	43.50	18605	13475
12.00-20/8.5	F-821	11.73	43.50	18605	13475
16/6-8/4.33	F-821	6.69	15.79	4480	3450
18/7-8/4.33	F-821 F-823	6.30	17.36	4929	3795
18/9-8/7.0	F-821	8.66	17.87	5864	4457
21/8-9/6.0	F-821 F-823	7.87	20.94	6190	4480
23/9-10/6.5	F-821 F-823	8.86	23.43	7525	5450
27/10-12/8.0	F-821	9.84	25.39	9261	6704
28/12.5-15/9.75	F-821	12.66	28.50	14995	11086
32/12.1-15/9.75	F-821	12.28	31.97	15745	11405
250-15/7.0	F-821 F-823	9.37	28.50	9615	6960
250-15/7.5	F-821 F-823	9.37	28.50	9615	6960
300-15/8.0	F-821 F-823	10.24	32.00	13190	9550
1100X330	F-822	13.35	42.87	33039	23921



F-831TR F-831TRT-2



F-832SM F-832SMT-2

**压配式（标准负荷）实芯轮胎技术参数（1）
PRESS-ON SOLID TIRE（1）**

规格 SIZE	花纹编号 PATT.NO.	花纹形式 PATT. TYPE	最大负荷（LBS）		
			转向轮 ROTATION	负荷轮 LOAD	
				≤10MPH	≤6MPH
81/2×4×4	F-832	SM	1260	1430	1260
9×5×5	F-832	SM	1740	1960	1740
10×4×61/4	F-832	SM	1420	1600	1420
*10×5×61/4	F-832	SM	1878	2125	1878
10×6×61/4	F-832	SM	2300	2600	2300
10×7×61/4	F-832	SM	2750	3100	2750
*10×4×61/2	F-832	SM	1430	1618	1430
	F-831	TR	1430	1618	1430
10×5×61/2	F-832	SM	1840	2070	1840
	F-831	TR	1840	2070	1840
*10×6×61/2	F-832	SM	2249	2528	2249
	F-831	TR	2249	2528	2249
*101/2×5×61/2	F-832	SM	1943	2197	1943
	F-831	TR	1943	2197	1943
*101/2×6×61/2	F-832	SM	2418	2730	2418
	F-831	TRTR	2418	2730	2418
*14×5×10	F-831	SM	1743	1917	1743
*14×8×10	F-832	SM	2723	2775	2723
	F-832	SMT-2			
	F-832	TR	2520	2850	2520
	F-831	TRT-2	2520	2850	2520
	F-831	SM			
15×6×111/4	F-832	TR	3120	3530	3120
	F-831	SM	3120	3530	3120
15×7×111/4	F-832	SM	3720	4210	3720
15×8×111/4	F-832	SM	4320	4890	4320
15×9×111/4	F-832	SM	4998	5655	4998
101/2×5×5	F-831	SM	1990	2250	1990
	F-832	TR	1990	2250	1990
101/2×6×5	F-831	SM	2530	2860	2530
	F-832	TR	2530	2860	2530
12×5×8	F-831	TR	2021	2294	2021
13×31/2×8	F-831	SM	1430	1610	1430
	F-832	TR	1430	1610	1430
13×41/2×8	F-831	SM	2030	2300	2030
	F-832	TR	2030	2300	2030

**压配式（标准负荷）实芯轮胎技术参数（2）
PRESS-ON SOLID TIRE（2）**

规格 SIZE	花纹编号 PATT.NO.	花纹形式 PATT. TYPE	最大负荷（LBS）		
			转向轮 ROTATION	负荷轮 LOAD	
				≤10MPH	≤6MPH
*13×51/2×8	F-831	SM	2639	2983	2639
	F-832	TR	2639	2983	2639
131/2×41/2×8	F-831	SM	2080	2350	2080
	F-832	TR	2080	2350	2080
131/2×51/2×8	F-831	SM	2730	3080	2730
	F-832	TR	2730	3080	2730
*131/2×61/2×8	F-831	TR	3380	3809	3380
	F-832	SM	3380	3809	3380
*131/2×71/2×8	F-831	TR	4030	4478	4030
	F-832	SM	4030	4478	4030
	F-831	TR			
14×41/2×8	F-832	SM	2120	2390	2120
	F-832	SMT-2	2120	2390	2120
	F-831	TRT-2	2120	2390	2120
151/2×5×10	F-831	TR	2670	3010	2670
	F-832	SM	2670	3010	2670
151/2×6×10	F-831	TR	3380	3820	3380
	F-832	SM	3380	3820	3380
16×41/2×101/2	F-832	SM	2360	2670	2360
	F-831	TR	2360	2670	2360
16×5×101/2	F832	SM	2730	3090	2730
	F-832	SMT-2	2730	3090	2730
	F-831	TRT-2	2730	3090	2730
	F-831	TR			
16×6×101/2	F-832	SM	3460	3920	3460
	F-832	SMT-2	3460	3920	3460
	F-831	TRT-2	3460	3920	3460
	F-831	TR			
16×7×101/2	F-831	TR	4200	4750	4200
	F-832	SM	4200	4750	4200
161/4×4×111/4	F-832	SMT-2SM	2040	2310	2040
	F-831	TRT-2	2040	2310	2040
161/4×5×111/4	F-832	TR	2760	3120	2760
	F-832	SM	2760	3120	2760
	F-831	SM			

压配式 (标准负荷) 实芯轮胎技术参数 (3)
PRESS-ON SOLID TIRE (3)

规格 SIZE	花纹编号 PATT.NO.	花纹形式 PATT. TYPE	最大负荷 (LBS)		
			转向轮 ROTATION	负荷轮 LOAD	
			≤10MPH	≤6MPH	≤10MPH
161/4×6×111/4	F-831	TR	3480	3930	3480
	F-832	SM			
	F-832	SMT-2			
	F-831	TRT-2			
161/4×7×111/4	F-831	TR	4190	4740	4190
	F-832	SM			
	F-832	SMT-2			
	F-831	TRT-2			
*161/4×8×111/4	F-832	TR	4250	4900	4250
*161/4×9×111/4	F-831	SM	4310	5070	4310
	F-832	SMT-2			
*18×5×14	F-832	SM	2910	3290	2910
18×7×14	F-832	SMT-2	4320	4890	4320
18×8×14	F-832	TRT-2	5030	5680	5030
	F-831	SMT-2			
18×9×14	F-832	SM	5730	6480	5730
	F-831	SM			
*20×5×16	F-832	SM	3170	3580	3170
20×6×16	F-832	TR	3920	4440	3920
20×7×16	F-832	SM	4680	5310	4680
20×8×16	F-832	TR	5460	6170	5460
	F-831	SM			
*20×9×16	F-831	SM	6200	7020	6200
	F-832	SM			
17×5×121/8	F-831	SM	2850	3230	2850
	F-832	TR			
18×5×121/8	F-831	SM	2980	3360	2980
	F-832	TR			
	F-832	SM			
18×6×121/8	F-831	TR	3800	4290	3800
	F-832	SM			
	F-832	SMT-2			
	F-831	TRT-2			
18×7×121/8	F-831	TR	4620	5220	4620
	F-832	SM			
	F-832	SMT-2			
	F-831	TRT-2			
18×8×121/8	F-831	TR	5440	6150	5440
	F-832	SM			
	F-832	SMT-2			
	F-831	TRT-2			
18×9×121/8	F-831	TR	6270	7080	6270
	F-832	SM			
	F-832	SMT-2			
	F-831	TRT-2			
21×5×15	F-831	TR	3330	3770	3330
	F-832	SM			
	F-832	SMT-2			
	F-831	TRT-2			

压配式 (标准负荷) 实芯轮胎技术参数 (4)
PRESS-ON SOLID TIRE (4)

规格 SIZE	花纹编号 PATT.NO.	花纹形式 PATT. TYPE	最大负荷 (LBS)		
			转向轮 ROTATION	负荷轮 LOAD	
			≤10MPH	≤6MPH	≤10MPH
21x6x15	F-831	TR	4270	4820	4270
	F-832	SM			
	F-832	SMT-2			
	F-831	TRT-2			
21x7x15	F-831	TR	5200	5870	5200
	F-832	SM			
	F-832	SMT-2			
	F-831	TRT-2			
21x8x15	F-831	TR	6130	6930	6130
	F-832	SM			
	F-832	SMT-2			
	F-831	TRT-2			
21x9x15	F-831	TR	7060	7980	7060
	F-832	SM			
	F-832	SMT-2			
	F-831	TRT-2			
*22x41/2x16	F-831	TR	2964	3367	2964
	F-832	SM			
	F-831	TR			
	F-832	SM			
22x5x16	F-832	SM	3450	3900	3450
	F-832	SMT-2			
	F-831	TRT-2			
	F-831	TR			
22x6x16	F-832	SM	4420	4990	4420
	F-831	TRT-2			
	F-831	TR			
	F-832	SM			
22x7x16	F-831	TRT-2	5380	6080	5380
	F-832	SM			
	F-832	SMT-2			
	F-831	TRT-2			
22x8x16	F-831	TR	6340	7170	6340
	F-832	SM			
	F-832	SMT-2			
	F-831	TRT-2			
22x9x16	F-831	TR	7310	8260	7310
	F-832	SM			
	F-832	SMT-2			
	F-831	TRT-2			
22x10x16	F-832	SM	8270	9350	8270
22x12x16	F-831	TR	10200	11530	10200
	F-832	SM			
22x14x16	F-831	TR	12130	13710	12130
	F-832	SM			
22x16x16	F-831	TR	14050	15890	14050
	F-832	SM			
28x12x22	F-831	TRT-2	12220	13820	12220
36x16x30	F-822	SMT-2	20330	22990	20330



E3/L3



E4/L4



G2



L5



L5S

OTR TIRE

SIZE	P.R.	RIM WIDTH	New Tire Section Width (mm)	New Tire Overall Diameter (mm)	Max Load (kg)		Pressure(kpa)		TT/TL	PATT.NO
					10km/h	50km/h	10km/h	50km/h		
13.00-24	12	8.00TG	330	1280	5600		450		TL	E4/L4
	14				6150		525			
14.00-24	24	10.00W,10.0	375	1420	9500	5150	850	575	TT	E4/L4
	28				10000	5600	925	650		
16.00-25	28	11.25/2.0	430	1546	11500	6700	750	575	TT/TL	E4/L4
	8				4750	2800	225	150		
17.5-25	12	14.00/1.5	445	1350/1400	6150	3650	350	225	TT/TL	E3/L3
	16				7300	4250	475	300		
	20				8250	5450	350	275		
20.5-25	16	17.00/2.0	520	1490/1548	9500	6000	450	325	TT/TL	E3/L3
	20				9500	6150	300	225		
23.5-25	20	19.50/2.5	595	1615/1672	10900	7300	375	300	TT/TL	E3/L3
	24				12500	8000	475	350		
26.5-25	24	22.0/3.0	675	1750/1798	14000	9250	400	300	TT/TL	E3/L3,L5
	28				15500	10000	475	350		
29.5-25	22	25.00/3.5	750	1875/1923	15000	1000	325	250	TL	E3/L3
	28				17500	11500	425	325		
29.5-29	28	25.00/3.5	750	2023	19000	12100	425	325	TL	E3/L3
	32				17500	10000	750	575		
18.00-33	36	13.00/2.5	495	1877	18500	10600	850	625	TL	E4/L4
	32				21200	12100	650	500		
21.00-35	36	15.00/3.0	575	2053	23000	12800	750	550	TL	E4/L4
	42				29000	16500	750	550		
24.00-35	48	17.00/3.5	650	2178	31500	18500	850	650	TL	E4/L4
	46				50000		675			
27.00-49	48	19.5/4.0	735	2703	43700	25000	775	575	TL	E4/L4
33.00-51	58	24.00/5.0	895	3060	39220		560		TL	E4/L4
36.00-51	58	26.0/5.0	990	3233	71000	41200	675	525	TL	E4/L4

AGRICULTURAL TIRE

SIZE	P.R.	Tread Depth (mm)	New Tire Overall Diameter (mm)	New Tire Section Width (mm)	Inflated Overall Diameter (mm)	Inflated Section Width (mm)	Rolling Circum. (mm)	Static Load Radius (mm)	Max Load		PSI	Max. Load		PSI	Foot Print (inch ²)		
									6MPH/25MP Field/Road Service			6MPH/25MP Field/Road Service			Hard Ground	Sand	
400/55-17.5	6	35	± 1.5%	± 2%	± 1.5%	± 2%	± 2.5%	± 2%									
	14	35	880	400	906	432	2640	409	875	17	520	7	149	299			
450/60-26.5	6	45	1160	400	1189	437	3480	542	1170	17	700	7	200	400			
	12	50	1260	500	1295	540	3755	580	1605	15	1070	7	306	613			
600/55-26.5	6	50	1350	600	1391	648	4050	615	1740	12	1325	7	378	756			
	14	50	1350	600	1391	648	4050	615	2980	29	1325	7	378	756			
600/55-30.5	6	50	1435	600	1475	648	4305	668	2245	16	1415	7	405	810			
	14	50	1435	600	1475	648	4305	668	3185	29	1415	7	405	810			
600/60-30.5	8	50	1495	600	1545	648	4485	695	2410	16	1520	7	435	870			
	14	50	1495	600	1545	648	4485	695	3420	29	1520	7	435	870			
700/65-30.5	8	55	1650	700	1711	755	4950	754	3090	13	2190	7	627	1255			
	14	55	1650	700	1711	755	4950	754	4325	23	2190	7	627	1255			
750/45-30.5	LI 143	50	1435	750	1497	804	4305	670	2725	17	1710	7	523	1045			
750/50-30.5	LI 146	50	1500	750	1577	804	4485	695	3000	17	1905	7	575	1151			
800/55-30.5	8	55	1650	800	1716	882	4950	754	3335	17	2530	7	725	1449			
700/55-34	8	55	1650	700	1705	755	4950	759	3000	13	2125	7	608	1216			
800/50-34	8	55	1650	800	1705	960	4950	759	3220	12	2445	7	700	1400			
600/60-38	8	50	1650	600	1712	648	5010	770	2705	16	1705	7	522	1044			
	14	50	1650	600	1712	648	5010	770	3840	29	1705	7	522	1044			
650/60-38	LI 148	60	1750	650	1797	702	5250	819	3150	17	1965	7	564	1127			
	LI 155	60	1750	650	1797	702	5250	819	3875	23	1965	7	564	1127			
710/65-38	LI 156	60	1860	710	1953	774	5580	849	4000	17	2490	7	712	1425			
	LI 161	60	1860	710	1953	774	5580	849	4750	23	2490	7	712	1425			
750/65-38	LI 159	60	1960	750	2008	803	5880	895	4375	17	2710	7	775	1550			
	LI 165	60	1960	750	2008	803	5880	895	5150	17	2710	7	775	1550			
850/50-38	LI 159	60	1860	850	1875	921	5580	850	4365	17	2930	7	839	1678			
850/60-38	LI 162	60	1960	850	2057	921	5880	895	4750	17	2980	7	852	1705			
	LI 169	60	1960	850	2057	921	5880	895	5800	17	2980	7	852	1705			
750/60-42	LI 157	60	1960	750	2030	803	5880	895	4125	17	2570	7	735	1470			
850/55-42	LI 161	60	1960	850	2067	921	5880	895	4650	17	2885	7	825	1651			

OTR TIRE

SIZE	P.R.	RIM WIDTH	New Tire Section Width (mm)	New Tire Overall Diameter (mm)	Max Load (kg)		Pressure(kpa)		TT/TL	PATT.NO
					10km/h	50km/h	10km/h	50km/h		
37.00-57	68	27.00/6.0	1072	3442		51500		530	TL	E-4
	52				80000	46200	550	425		
40.00-57	60	29.00/6.0	1095	3590	87500	50000	650	475	TL	E-4
	68				92500	54500	725	550		
35/65-33	24	28.00/3.5	890	2088	19000	11500	350	250	TL	L5
	30				21200	12600	425	300		
	36				23600	14500	525	375		

TEMCO INTERNATIONAL LIMITED

marketing@0086parts.com

TO BE DEVELOPPED 28